

Electrolux Dryers for OPL

30x30 & 45x45 stack, 35, 67, 83, 100 & 135 lb. capacities

High performance and significant energy savings.

Electrolux dryers are precision-engineered for efficiency, ease of use, and superior drying results. Perfect for hotels, motels, hospitals, nursing homes, gyms, salons, schools, and other facilities. You'll appreciate the "green" engineering, easy operation, and years of low maintenance.

Features and benefits:

- Optimal combination of gas consumption (Btu/hr) and airflow (CFM) provides the fastest drying with lowest energy consumption.
- Extra large doors make loading and unloading easy.
- Self-cleaning lint screen & large lint compartment for easy maintenance.
- Quiet operation. Designed to keep noise level below 70 dB (A).
- Reversing drum (standard) minimizes tangling and wrinkling. Improves dryer efficiency and makes flatwork finishing easier.
- Fresh air intake adapter acquires air from a location outside the dryer area. Useful when dryers are installed in interior or air-conditioned space.

35, 67 and 83 lb. dryer features:

- **Axial airflow** and tight construction for extremely low energy consumption
- **Compass Pro** program control
- Top Exhaust Kit (optional)

Residual Moisture Control:

The Residual Moisture Control (RMC) option is available in all Electrolux single pocket dryers. RMC prevents damage to garments caused by overdrying and reduces lint and wrinkles by automatically stopping the dryer when the exact pre-set moisture level is reached. The amount of residual moisture in the fabric is important for proper finishing. If the load is to be further processed by an ironer, RMC will shut the dryer off while there is still sufficient moisture for the ironer to work effectively. By not overdrying, you'll benefit from longer linen life and significant labor and energy savings.



Electrolux OPL Dryers available in 30x30, 45x45, 35, 67, 83, 100 and 135 lb. capacities. Available in stainless (optional) or wave front panel.

35, 67 and 83 lb. with Axial Airflow and Compass Pro control. Other options include: Stainless steel drum, RMC, Heat recovery system: Heat Recovery Pipes (HRP), fresh air intake, exhaust on top. Call for more information.



The future of professional laundry is here.

Electrolux is dedicated to providing you with the very best precision-engineered washers, dryers, and flatwork ironers. Production units are certified in accordance with ISO 9001 (Quality) and ISO 14001 (Environmental Management) standards, and products are CE labeled. Take control of your laundry operations with Electrolux Professional Laundry.

For more information, please visit www.laundrylux.com

Model	T4300		T4420		T5290		T5550		T5675		T4900		T41200	
Capacity (lb/kg)	2 x 30	2 x 13.5	2 x 45	2 x 20.41	35	16.1	67	30.5	83	37.5	100	45	135	60
Width (in/mm)	31 1/8	790	34 1/4	870	27 15/16	710	37 13/16	960	37 13/16	960	50 13/16	1290	50 13/16	1290
Depth (in/mm)	43 11/16	1110	52 5/8	1336	45 1/2	1155	51 3/4	1315	59 7/16	1510	51	1295	58 7/16	1485
Depth with door open (in/mm)	72 7/16	1840	85 5/8	2175	68 5/16	1735	83 11/16	2125	91 5/16	2320	94 1/2	2400	101 15/16	2590
Height Overall (in/mm)	76 3/8	1940	81 7/8	2078	65 15/16	1675	73 7/16	1855	73 7/16	1855	97 1/16	2465	97 1/16	2465
Height without heating unit (in/mm)	n/a		n/a		n/a		n/a		n/a		77 3/8	1965	77 3/8	1965
Door opening diameter (in/mm)	22 7/8	580	27	686	22 13/16	580	31 7/8	810	31 7/8	810	37	940	37	940
Cylinder volume (ft ³ /l)	10.6	300	14.6	414	10.2	290	19.4	550	23.8	675	31.8	900	42.4	1200
Crated Weight (lb/kg)	693	315	865	392	518	235	717	325	827	375	1100	500	1166	530
Utility Connections			(2) 8" or (1) 10"											
Exhaust duct diameter (in/mm)	8	200	(2) 203mm or (1) 254mm		8	200	10	250	10	250	12	315	12	315
Gas connection	1/2 NPT		3/4 MNPT		1/2 NPT		1/2 NPT		3/4 NPT		1 NPT		1 NPT	
Steam connection, inlet & condensate	n/a		n/a		1 NPT		1 NPT		1 NPT		1 NPT		1 NPT	
Energy Data														
Gas (Btu/hr)	2 x	71,700	2 X 94,000		71,700		112,700		143,400		219,000		280,000	
Airflow (ft ³ /min / m ³ /hr) (gas heat)	2 x 354	2 x 600	2 x 600 2 x 1020		360 / 610		550 / 940		670 / 1140		1354 / 2300		1765 / 3000	
Electric (kW) @ 208-240V/3Ø	2 x 18	n/a	18	30	13.5 or 18		24 or 32		24 or 32		32		72	
Airflow (ft ³ /min / m ³ /hr) (elec. heat)	2 x 354	2 x 600	n/a		325 / 550		550 / 940		670 / 1140		1354 / 2300		1765 / 3000	
Steam (lb/hr /kg/hr) (approximate)	n/a		n/a		80 / 36		118 / 54		150 / 68		315 / 143		315 / 143	
Airflow (ft ³ /min / m ³ /hr) (steam heat)	n/a		n/a		405 / 690		635 / 1080		810 / 1380		1354 / 2300		1765 / 3000	
Electrical Requirements														
Current, gas or steam, 120 V/60Hz (full load/circuit breaker)	2 x 9A / 2 x 15A		2 x 12A / 2 x 15A		7.5A (15A)		12A (20A)		12A (20A)		n/a		n/a	
Current, gas or steam, 208-240 V/60Hz/1Ø (full load/circuit breaker)	2 x 4.5A / 2 x 15A		5.50A / 15A		3.5A (15A)		8.5A (15A)		8.5A (15A)		n/a		n/a	
Current, gas or steam, 208-240 V/60Hz/3Ø (full load/circuit breaker)	n/a		n/a		3.75A (15A)		10A (15A)		10A (15A)		10A (15A)		10A (15A)	
Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)	2 x 50 / 2 x 65		n/a		14.4-18.9 (60A)		26.1-34.4 (110A)		26.1-34.4 (110A)		75 / 100 @ 480 Volts		90 / 125 @ 480 Volts	
Alternate Voltages														
Alternate voltages available. Contact Laundrylux Sales Department for information.														
Supply Pressures														
Natural Gas (inches H ₂ O/mbar)	6-10 / 15-25		6-12 / 15-30		3.5-10.5 / 9-26		3.5-10.5 / 9-26		3.5-10.5 / 9-26		6-10 / 15 - 25		6-10 / 15-25	
Propane (inches H ₂ O/mbar)	10-13 / 25-30		11-13 / 28-33		8-13 / 20-32		8-13 / 20-32		8-13 / 20-32		10-13 / 25-30		10-13 / 25-30	
Steam (psi/bar) (max)	n/a		145 / 10		145 / 10		145 / 10		145 / 10		145 / 10		145 / 10	
Exhaust back pressure (inches H ₂ O/mbar) (max)	1.57	3.9	0.6	1.5	2.2	5.5	2.6	6.48	3	7.5	0.37	1	0.37	1

Note: T4420S 45 lb. stack dryer - 208 volt, 1-phase not available. Use 120 volt model for 208 volt applications.

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, inverse-time, common-trip, industrial-type circuit breakers ONLY. Warranty void if not properly installed. Advise when placing order if dryers are for installation at altitudes in excess of 1000 feet above sea level, as this may require a gas-orifice change. Contact Laundrylux for more information and availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

ELECTROLUX DRYER CONTROL

Compass PRO available on 35, 67, and 83 lb. dryers • Selecta II on 30x30, 45x45, 100 and 135 lb. dryers



Compass Pro

- Large & clear display with control knob for easy program selection
- Easy access with user-friendly interface
- Language selection
- Drying program packages optimized for Economy, Care and Time
- Service program for adjustment of parameters
- USB Type B connection

Selecta II

- Precise control of temperature, residual moisture, program, time, reversing and cool-down selection.
- Displays selected program, remaining drying time, cool-down time and actual temperature.
- Comprehensive diagnostics and service functions.

Call today for information on the full line of Electrolux Professional washers, dryers, ironers, and low-cost financing & leasing.

Thinking of you

800.381.7222 • www.laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338
 Sales and Administration – Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@laundrylux.com
 Spare Parts – Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@laundrylux.com
 Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@laundrylux.com
 En Mexico: Llame gratis a este numero 001-800-010-1010

Your local independent authorized dealer